

Work Order ID 136833

September 10, 2015 11:03:59 AM

136833

Page 1

Item ID: D4956-15 Accept ***N900040100*** Setup Start ***NS1***
Revision ID: Stop ***NS2***
Item Name: Wearplate Fwd
Start Date: 9/10/2015 Start Qty: 2.00 *2* Cust Item ID:
Required Date: 9/24/2015 Req'd Qty: 2.00 *2* Customer:
Reference:

Approvals: Process Plan: SH Date: 20150910 Tooling: Date: Run Start ***NR1***
QC: Date: SPC (Y/N): Date: Stop ***NR2***

Sequence ID/ Work Center ID	Operation Description	Set Up/ Run Hours	Tool ID	Tool #	Plan Code	Accept Qty	Reject Qty	Reject Number	Insp. Stamp
--------------------------------	--------------------------	----------------------	---------	--------	--------------	---------------	---------------	------------------	----------------

Draw Nbr	Revision Nbr								
D4956	A								

100		0.00							
-----	--	------	--	--	--	--	--	--	--

100

Waterjet Memo 0.01 (2) DC15/09/30

FLOW CNC Waterjet 1-Cut as per Dwg Dwg Rev: A Prog Rev: A

2-Deburr if necessary

110	QC2- Inspect parts off machine FAI/FAIB	0.00							
-----	---	------	--	--	--	--	--	--	--

110

QC Memo 0.00 (2) DC15/09/30

Quality Control

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐					
Date :		Step #:		QTY Effective :			MRB (QSI042) Approval		
Description Work Order Deviation				Disposition				Completed By	
								Lead hand / Supervisor Approval Verification	
								QC / QA Coordinator Approval	
Root Cause		FAULT CATEGORY							
Environment ☐ Design ☐ Doc/Data ☐ Equip/Tooling ☐ Handling/Pre ☐ Material ☐ Internal Transport ☐ Tribal Knowledge ☐ LOA ☐ Substation ☐ Past Expiry Date ☐ Misidentified ☐	No Re-verification ☐ Operator ☐ Offset/Setup ☐ Supplier ☐ Training ☐ Use for Testing ☐ Poor Information ☐ Rushing ☐ Product Improvement ☐ Process Improvement ☐ Manufacturing Process ☐ Past Due ☐	Pressure/Forced ☐ Bending ☐ Centre Not Concentric ☐ Cracks ☐ Crimp/Kink/Ripple/Wave ☐ Cuffs ☐ Crushing ☐ Heat Treat ☐ Wave/Twist in Tube ☐ Marks/Chatter ☐	Temperature/Cure ☐ Set-up ☐ BOM/Route ☐ Broken/Damage/Defect ☐ Inspection Incomplete/Unqualified ☐ Contamination ☐ Countersink ☐ Cut Too Short ☐ Instructions Incomplete/Unclear ☐ Drill Holes ☐	Power Loss/Surge ☐ Folio/Program ☐ Grain ☐ Weld ☐ Wrong Stock Pulled ☐ Out of Sequence ☐ Off-set ☐ Misabeled ☐ Fit/Function ☐ Misaligned/off center ☐	Positioned Wrong ☐ Outside Dimensions ☐ Over/Under tolerance ☐ Part Incorrect ☐ Part Lost/Missing ☐ Part Moved ☐ Drawing ☐ Finish ☐ Misread ☐ Turning Sequence ☐	OTHER : ☐			

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐					
Date :		Step #:		QTY Effective :			MRB (QS1042) Approval		
Description Work Order Deviation				Disposition				Completed By	
								Lead hand / Supervisor Approval Verification	
								QC / QA Coordinator Approval	
Root Cause		FAULT CATEGORY							
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐				
Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐				
Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐				
Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐				
Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐				
Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐				
Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐				
Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐				
LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐				
Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐				
Past Expiry Date ☐	Manufacturing Process ☐	OTHER : _____							
Misidentified ☐	Past Due ☐								

Work Order ID 136833

September 10, 2015 11:03:59 AM

136833

Page 3

Item ID: D4956-15 Accept ***N900040100*** Setup Start ***NS1***
 Revision ID: Stop ***NS2***
 Item Name: Wearplate Fwd
 Start Date: 9/10/2015 Start Qty: 2.00 ***2*** Cust Item ID:
 Required Date: 9/24/2015 Req'd Qty: 2.00 ***2*** Customer:
 Reference:

Approvals: Process Plan: _____ Date: _____ Tooling: _____ Date: _____ Run Start ***NR1***
 QC: _____ Date: _____ SPC (Y/N): _____ Date: _____ Stop ***NR2***

Sequence ID/ Work Center ID	Operation Description	Set Up/ Run Hours	Tool ID	Tool #	Plan Code	Accept Qty	Reject Qty	Reject Number	Insp. Stamp
150		0.00							DAS 41 9-89
150						2			
HandFinish	Memo	0.00							
Hand Finishing	1- After finish, coat entire top (concave) surface as per note 2 dwg D4956. TEXTURED COATING B#: <u>132664</u>								15-9-30
160	QC3- Inspect Part Finish	0.00							DAS 38 9-89
160						(2)			
QC	Memo	0.00							
Quality Control									OCT 01 2015
170	Identify as per dwg & Stock Location <u>FP-002</u>	0.00							
170									
Packaging	Memo	0.00							
Packaging	LOCATION : FP002								x2 ϕ H 10/10/05

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____	DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐	AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐			
Date : _____	Step #: _____	QTY Effective : _____		MRB (QS1042) Approval	
Description Work Order Deviation		Disposition		Completed By	
				Lead hand / Supervisor Approval Verification	
				QC / QA Coordinator Approval	
Root Cause Environment ☐ Design ☐ Doc/Data ☐ Equip/Tooling ☐ Handling/Pre ☐ Material ☐ Internal Transport ☐ Tribal Knowledge ☐ LOA ☐ Substation ☐ Past Expiry Date ☐ Misidentified ☐ No Re-verification ☐ Operator ☐ Offset/Setup ☐ Supplier ☐ Training ☐ Use for Testing ☐ Poor Information ☐ Rushing ☐ Product Improvement ☐ Process Improvement ☐ Manufacturing Process ☐ Past Due ☐		FAULT CATEGORY Pressure/Forced ☐ Bending ☐ Centre Not Concentric ☐ Cracks ☐ Crimp/Kink/Ripple/Wave ☐ Cuffs ☐ Crushing ☐ Heat Treat ☐ Wave/Twist in Tube ☐ Marks/Chatter ☐ Temperature/Cure ☐ Set-up ☐ BOM/Route ☐ Broken/Damage/Defect ☐ Inspection Incomplete/Unqualified ☐ Contamination ☐ Countersink ☐ Cut Too Short ☐ Instructions Incomplete/Unclear ☐ Drill Holes ☐ Power Loss/Surge ☐ Folio/Program ☐ Grain ☐ Weld ☐ Wrong Stock Pulled ☐ Out of Sequence ☐ Off-set ☐ Misabeled ☐ Fit/Function ☐ Misaligned/off center ☐ Positioned Wrong ☐ Outside Dimensions ☐ Over/Under tolerance ☐ Part Incorrect ☐ Part Lost/Missing ☐ Part Moved ☐ Drawing ☐ Finish ☐ Misread ☐ Turning Sequence ☐			
OTHER : _____					

Work Order ID 136833

September 10, 2015 11:03:59 AM

136833

Page 4

Item ID: D4956-15 Accept ***N900040100*** Setup Start ***NS1***
Revision ID: Stop ***NS2***
Item Name: Wearplate Fwd
Start Date: 9/10/2015 Start Qty: 2.00 ***2*** Cust Item ID:
Required Date: 9/24/2015 Req'd Qty: 2.00 ***2*** Customer:
Reference:

Approvals: Process Plan: _____ Date: _____ Tooling: _____ Date: _____ Run Start ***NR1***
QC: _____ Date: _____ SPC (Y/N): _____ Date: _____ Stop ***NR2***

Sequence ID/ Work Center ID	Operation Description	Set Up/ Run Hours	Tool ID	Tool #	Plan Code	Accept Qty	Reject Qty	Reject Number	Insp. Stamp
180	QC21- Final Inspection - Work Order Release	0.00							
180									
QC	Memo	0.00							
Quality Control									

MLJ OCT 06 2015

SH 20151205

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____	DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐	AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐			
Date :	Step #:	QTY Effective :		MRB (QS1042) Approval	
Description Work Order Deviation			Disposition		
			Completed By		
			Lead hand / Supervisor Approval Verification		
			QC / QA Coordinator Approval		
Root Cause		FAULT CATEGORY			
Environment ☐ Design ☐ Doc/Data ☐ Equip/Tooling ☐ Handling/Pre ☐ Material ☐ Internal Transport ☐ Tribal Knowledge ☐ LOA ☐ Substation ☐ Past Expiry Date ☐ Misidentified ☐	No Re-verification ☐ Operator ☐ Offset/Setup ☐ Supplier ☐ Training ☐ Use for Testing ☐ Poor Information ☐ Rushing ☐ Product Improvement ☐ Process Improvement ☐ Manufacturing Process ☐ Past Due ☐	Pressure/Forced ☐ Bending ☐ Centre Not Concentric ☐ Cracks ☐ Crimp/Kink/Ripple/Wave ☐ Cuffs ☐ Crushing ☐ Heat Treat ☐ Wave/Twist in Tube ☐ Marks/Chatter ☐	Temperature/Cure ☐ Set-up ☐ BOM/Route ☐ Broken/Damage/Defect ☐ Inspection Incomplete/Unqualified ☐ Contamination ☐ Countersink ☐ Cut Too Short ☐ Instructions Incomplete/Unclear ☐ Drill Holes ☐	Power Loss/Surge ☐ Folio/Program ☐ Grain ☐ Weld ☐ Wrong Stock Pulled ☐ Out of Sequence ☐ Off-set ☐ Mislabelled ☐ Fit/Function ☐ Misaligned/off center ☐	Positioned Wrong ☐ Outside Dimensions ☐ Over/Under tolerance ☐ Part Incorrect ☐ Part Lost/Missing ☐ Part Moved ☐ Drawing ☐ Finish ☐ Misread ☐ Turning Sequence ☐
OTHER : _____					

Picklist Print

September 10, 2015 11:04:06 AM

Page 1

Work Order ID: 136833

136833

Parent Item: D4956-15

D4956-15

Parent Item Name: Wearplate Fwd

Start Date: 9/10/2015

Required Date: 9/24/2015

Start Qty: 2.00

Required Qty: 2.00

Comments: IPP REV:A 14.04.22 NEW ISSUE DD VERF:JLM

Component Item ID/ Item Name	Replacement Item ID	Mfg/ Purch	Bin Item	Primary Location	Last Location	Route Seq ID	Unit of Measure	Qty on Hand	Qty per Kit	Total Qty	Qty Issued	Date Issued	Status
---------------------------------	------------------------	---------------	-------------	---------------------	------------------	-----------------	--------------------	----------------	-------------	--------------	---------------	----------------	--------

M304S20GA

Purchased

No

sf

346.8623

2

M304S20GA

304/316 .040 Sheet

DUIS/09/30

Location

Loc Qty

Loc Code

MAT

22.6

m131700

22.6

2.3

MAT020

324.2623

m130345


1.3139

m131060


90.2484

m132387


232.7




D4956-11F FLAT PATTERN



D4956-11 WEARSHOE
(MAKE FROM D4956-11F)



D4956-13F FLAT PATTERN



D4956-13 WEARSHOE
(MAKE FROM D4956-13F)


NOTES

- 1) MATERIAL: AISI 304/316 SS SHEET, 0.038 THICK (20 GAUGE)
PER AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC M304S20GA
- 2) FINISH: COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.020-0.040 THICK, PER DART QSI 005 4.0
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1 (FINE POINT PAINT MARKER)
- 7) WEIGHT: D4956-11 = 0.68 lbs; D4956-13 = 0.82 lbs
- 8) SYMMETRY: ABOUT CENTERLINE


RELEASED
2014-04-17

136833 SK 20150910

REV.	NEW ISSUE	DESCRIPTION	MB	13.09.26
DESIGN			BY	DATE
DRAWN			DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED				
MFG. APPR.		DRAWING NO. D4956	REV. A	SHEET 1 OF 8
APPROVED		TITLE WEARSHOE	SCALE	NTS
DE APPR.				
DATE	13.09.26	COPYRIGHT © 2013 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR DISCLOSED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.		



D4956-15F FLAT PATTERN




D4956-15 WEARSHOE
(MAKE FROM D4956-15F)

NOTES


- 1) MATERIAL: AISI 304/316 SS SHEET, 0.038 THICK (20 GAUGE)
PER AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC M304S20GA
- 2) FINISH: COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.020-0.040 THICK, PER DART QSI 005 4.9
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1 (FINE POINT PAINT MARKER)
- 7) WEIGHT: 0.95 lbs
- 8) SYMMETRY: ABOUT CENTERLINE

DESIGN		DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED	A.P.	DRAWING NO.	REV. A
MFG. APPR.		D4956	SHEET 2 OF 8
APPROVED		TITLE	SCALE
DE APPR.		WEARSHOE	NTS
DATE	13.09.26	COPYRIGHT © 2013 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	


RELEASED
2014-04-17
MD




D4956-21F FLAT PATTERN



D4956-25F FLAT PATTERN



D4956-21 WEARSHOE
(MAKE FROM D4956-21F)



D4956-25 WEARSHOE
(MAKE FROM D4956-25F)


NOTES

- 1) MATERIAL: AISI 304/316 SS SHEET, 0.038 THICK (20 GAUGE)
PER AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC M304S20GA
- 2) FINISH: COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.020-0.040 THICK, PER DART QSI 005 4.9
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1 (FINE POINT PAINT MARKER)
- 7) WEIGHT: D4956-21 = 0.82 lbs; D4956-25 = 0.58 lbs
- 8) SYMMETRY: ABOUT CENTERLINE

RELEASED
2014-04-17
MD

DESIGN	J	DART AEROSPACE LTD	
DRAWN	J	HAWKESBURY, ONTARIO, CANADA	
CHECKED	A.P.	DRAWING NO.	REV. A
MFG. APPR.	S	D4956	SHEET 3 OF 8
APPROVED	JS	TITLE	SCALE
DE APPR.	J	WEARSHOE	NTS
DATE	13.09.26	COPYRIGHT © 2013 BY DART AEROSPACE LTD	
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.			

R0.25
TOOLING NOTCH
TYP



D4956-23F FLAT PATTERN




D4956-23 WEARSHOE
(MAKE FROM D4956-23F)

NOTES


- 1) MATERIAL: AISI 304/316 SS SHEET, 0.038 THICK (20 GAUGE)
PER AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC M304S20GA
- 2) FINISH: COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.020-0.040 THICK, PER DART QSI 005 4.9
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1 (FINE POINT PAINT MARKER)
- 7) WEIGHT: 1.29 lbs
- 8) SYMMETRY: ABOUT CENTERLINE

RELEASED
2014-04-17


DESIGN		DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED	AP	DRAWING NO.	REV. A
MFG. APPR.	BB	D4956	SHEET 4 OF 8
APPROVED	MO	TITLE	SCALE
DE APPR.		WEARSHOE	NTS
DATE	13.09.26	COPYRIGHT © 2013 BY DART AEROSPACE LTD	
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESSED UNDERSTANDING THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.			




D4956-31F FLAT PATTERN



D4956-31 WEARSHOE
(MAKE FROM D4956-31F)



D4956-33F FLAT PATTERN




D4956-33 WEARSHOE
(MAKE FROM D4956-33F)

NOTES


- 1) MATERIAL: AISI 304/316 SS SHEET, 0.038 THICK (20 GAUGE)
PER AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC M304S20GA
- 2) FINISH: COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.020-0.040 THICK, PER DART QSI 005 4.9
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1 (FINE POINT PAINT MARKER)
- 7) WEIGHT: D4956-31 = 0.57 lbs; D4956-33 = 0.61 lbs
- 8) SYMMETRY: ABOUT CENTERLINE

DESIGN		DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED	AP	DRAWING NO.	REV. A
MFG. APPR.		D4956	SHEET 5 OF 8
APPROVED		TITLE	SCALE
DE APPR.		WEARSHOE	NTS
DATE	13.09.26	COPYRIGHT © 2013 BY DART AEROSPACE LTD	
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR REPRODUCED IN ANY MANNER WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.			


RELEASED
2014-04-17




D4956-35F FLAT PATTERN



D4956-35 WEARSHOE
(MAKE FROM D4956-35F)



D4956-37F FLAT PATTERN




D4956-37 WEARSHOE
(MAKE FROM D4956-37F)

NOTES


- 1) MATERIAL: AISI 304/316 SS SHEET, 0.038 THICK (20 GAUGE)
PER AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC M304S20GA
- 2) FINISH: COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.020-0.040 THICK, PER DART QSI 005 4.9
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1 (FINE POINT PAINT MARKER)
- 7) WEIGHT: D4956-35 = 0.60 lbs; D4956-37 = 0.76 lbs
- 8) SYMMETRY: ABOUT CENTERLINE

DESIGN		DART AEROSPACE LTD
DRAWN		HAWKESBURY, ONTARIO, CANADA
CHECKED	AP	DRAWING NO. REV. A
MFG. APPR.		D4956 SHEET 6 OF 8
APPROVED		TITLE SCALE
DE APPR.		WEARSHOE NTS
DATE	13.09.26	COPYRIGHT © 2013 BY DART AEROSPACE LTD


RELEASED
2014-04-17




D4956-39F FLAT PATTERN



D4956-41F FLAT PATTERN



D4956-39 WEARSHOE
(MAKE FROM D4956-39F)




D4956-41 WEARSHOE
(MAKE FROM D4956-41F)

NOTES


- 1) MATERIAL: AISI 304/316 SS SHEET, 0.038 THICK (20 GAUGE)
PER AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC M304S20GA
- 2) FINISH: COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.020-0.040 THICK, PER DART QSI 005 4.9
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1 (FINE POINT PAINT MARKER)
- 7) WEIGHT: D4956-39 = 0.86 lbs; D4956-41 = 0.68 lbs
- 8) SYMMETRY: ABOUT CENTERLINE

RELEASED
2014-04-17


DESIGN		DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED		DRAWING NO.	REV. A
MFG. APPR.		D4956	SHEET 7 OF 8
APPROVED		TITLE	SCALE
DE APPR.		WEARSHOE	NTS
DATE	13.09.26	COPYRIGHT © 2013 BY DART AEROSPACE LTD	
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION (PRECEDENT) AEROSPACE LTD.			



DETAIL A C8-1 C4-1
C8-2
C8-3 C1-3
C2-4
C8-5 C2-5
C8-6 C2-6
C4-7 C3-7



DETAIL B B6-1 B2-1
B3-2
B6-3 B1-3
B2-4
B4-7 B1-7



SECTION C-C B7-1 B3-1
B5-2
B7-3 B3-3
B6-4
B7-5 B3-5
B7-6 B3-6
B7-7 B3-7

RELEASED
2014-04-17
MP

DESIGN		DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED	AP	DRAWING NO. D4956	REV. A
MFG. APPR.		TITLE WEARSHOE	SHEET 6 OF 8
APPROVED		SCALE	NTS
DE APPR.		COPYRIGHT © 2013 BY DART AEROSPACE LTD	
DATE	13.09.26	THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

